

Type designation: Isolating transformer 230 V - 1750 VA / 230 V - 1750 VA
Type: ETTV 3500
Item number: 1053

Standard: VDE 0570 Teil 2-4, EN 61558-2-4
Version: stationary
Construction: encapsulated with high insulating polyurethane, carrying handle
Short circuit strength: non short circuit proof
Max. ambient temperature: + 40°C
Insulation class: E
Protection index: IP 65
Safety class: 2
Weight approximately: 45 kg
Dimensions approximately: 240 x 240 x 325 mm (width x height x depth)
Fixing / grid: Aluminium base plate (EN AW 6082) / thread 4x M8 / 150 x 200 mm
Installation position: Distance at least 10 mm to the contact surface for sufficient air convection
Connection input: Phönix Contact plug / pole 1 = L1 / pole 2 = N / ID 15 85 21 0
Connection output: Phönix Contact socket / pole 1 = 1L1 / pole 2 = 1L2 / ID 15 85 22 3
Connecting cable pluggable: Phönix Contact case ID 14 19 25 8 with approximately 2 m power cord H07RN-F 2x1,5 mm², 100 mm stripped, ends with wire end ferrules

Power: 3500 VA
Input voltage (PRI): 230 V
Output 1 (SEC 1): 230 V / 7,61 A / 1750 VA
Output 2 (SEC 2): 230 V / 7,61 A / 1750 VA
Frequency: 50-60 Hz
Test voltage: 4000 V / 50 Hz

Application: The stationary isolating transformer guaranteed the safe galvanic isolation of the input and output sides.
Isolating transformers may be used to set up protective separation as a protective measure in accordance with VDE 0100.

Optional on request: CEE-sockets, country-specific voltages, customer specific connection cable



Optionally with mounting rails
Fixing / grid: : 4x M8 / 290 x 200 mm



Subjects to change!
Original may differ from photo!