

---

Type designation:	Isolating transformer 900 VA / 230 V / 230 V
Type:	ETTV 900
Item number:	02-10900

---

Standard:	VDE 0570 Teil 2-4, EN 61558-2-4
Version:	stationary
Construction:	encapsulated with high insulating polyurethane
Short circuit strength:	non inherently short circuit proof
Installation position:	vertical with the cable glands down
Max. ambient temperature:	+ 40°C
Insulation class:	E
Protection index:	IP 65
Safety class:	2
Weight:	17 kg
Fixing holes:	4x 6,2 mm
Dimensions approximately:	215 x 143 x 333 mm (width x height x depth)
Connection input:	1x PG 13,5 cable gland, screw-type terminals 1,5 – 4 mm <sup>2</sup> 2 poles
Connection output:	1x PG 13,5 cable gland, screw-type terminals 1,5 – 4 mm <sup>2</sup> 2 poles
Short circuit strength input:	Glass body fuse IEC 60127-2/3
Overload protection input:	Fail-safe temperature switch

---

Power:	900 VA
Input voltage:	230 V
Output voltage:	230 V
Output current:	3,91 A
Frequency:	50-60 Hz
Test voltage:	4000 V / 50 Hz

---

Application:	The stationary isolating transformer guaranteed the safe galvanic isolation of the input and output sides Isolating transformers may be used to set up protective separation as a protective measure in accordance with VDE 0100. Only one device on each secondary winding of an isolation transformer may be connected in accordance with BGI 594.
--------------	---

---

Optional on request:	2m power cord with contour plug, country-specific voltages, safety transformers with low voltage < 50 V
----------------------	---

---



Subjects to change!