

---

Type designation: Isolating transformer 2500 VA / 230 V / 230 V  
Type: ETTV 2500  
Item number: 01-12500

---

Standard: VDE 0570 Teil 2-4, EN 61558-2-4, IEC 61558-2-4  
Version: transportable  
Construction: encapsulated with high insulating polyurethane, carrying handle  
Short circuit strength: non inherently short circuit proof  
Max. ambient temperature: + 40°C  
Insulation class: E  
Protection index: IP 54  
Safety class: 2  
Weight: 41 kg  
Dimensions approximately: 240 x 280 x 350 mm (width x height x depth)  
Connection input: 2m power cord with contour plug CEE 7/17  
Connection output: SCHUKO socket, PE potential free  
Protection input: Thermal protection switch

---

Power: 2500 VA  
Input voltage: 230 V  
Output voltage: 230 V  
Output current: 10,87 A  
Frequency: 50-60 Hz  
Test voltage: 4000 V / 50 Hz

---

Application: The transportable isolating transformer guaranteed the safe galvanic isolation of the input and output sides  
Isolating transformers may be used to set up protective separation as a protective measure in accordance with VDE 0100. Only one device on each secondary winding of an isolation transformer may be connected in accordance with BGI 594.

---

Optional on request: Sockets USA, UK, UAE, China, France, Switzerland, Brasil, Australia, etc, country-specific voltages, safety transformers with low voltage < 50 V, three-phase version, CEE or low voltage sockets

---



Subjects to change!