

---

|                   |   |
|-------------------|---|
| Type designation: | Isolating transformer 2500 VA / 230 V / 230 V |
| Type:             | ETTV 2500                                     |
| Item number:      | 01-12500                                      |

---

|                           |   |
|---------------------------|---|
| Standard:                 | VDE 0570 Teil 2-4, EN 61558-2-4, IEC 61558-2-4                  |
| Version:                  | transportable   |
| Construction:             | encapsulated with high insulating polyurethane, carrying handle |
| Short circuit strength:   | non inherently short circuit proof                              |
| Max. ambient temperature: | + 40°C  |
| Insulation class:         | E   |
| Protection index:         | IP 54   |
| Safety class:             | 2   |
| Weight:                   | 41 kg   |
| Dimensions approximately: | 240 x 280 x 350 mm (width x height x depth)                     |
| Connection input:         | 2m power cord with contour plug CEE 7/17                        |
| Connection output:        | SCHUKO socket, PE potential free                                |
| Protection input:         | Thermal protection switch                                       |

---

|                 |                |
|-----------------|----------------|
| Power:          | 2500 VA        |
| Input voltage:  | 230 V          |
| Output voltage: | 230 V          |
| Output current: | 10,87 A        |
| Frequency:      | 50-60 Hz       |
| Test voltage:   | 4000 V / 50 Hz |

---

|              |   |
|--------------|---|
| Application: | <p>The transportable isolating transformer guaranteed the safe galvanic isolation of the input and output sides</p> <p>Isolating transformers may be used to set up protective separation as a protective measure in accordance with VDE 0100. Only one device on each secondary winding of an isolation transformer may be connected in accordance with BGI 594.</p> |
|--------------|---|

---

|                      |   |
|----------------------|---|
| Optional on request: | Sockets USA, UK, UAE, China, France, Switzerland, Brasil, Australia, etc, country-specific voltages, safety transformers with low voltage < 50 V, three-phase version, CEE or low voltage sockets |
|----------------------|---|

---



Subjects to change!