
Type designation:	Isolating transformer 3500 VA / 230 V-1750 VA / 230 V-1750 VA
Type:	ETTV 3500
Item number:	1045

Standard:	VDE 0570 Teil 2-4, EN 61558-2-4
Version:	transportable, outputs are galvanically isolated against each other
Construction:	encapsulated with high insulating polyurethane, carrying handle
Short circuit strength:	non inherently short circuit proof
Max. ambient temperature:	+ 30°C
Insulation class:	E
Protection index:	IP 54
Safety class:	2
Weight:	45 kg
Dimensions approximately:	240 x 280 x 350 mm (width x height x depth)
Connection input:	2m power cord with contour plug CEE 7/17
Connection output:	SCHUKO socket, PE potential free
Protection input:	Thermal protection switch
Protection output 1+2:	Glass body fuse IEC 60127-2/3

Power:	3500 VA
Input voltage:	230 V
Output voltage 1:	230 V / 7,61 A / 1750 VA
Output voltage 2:	230 V / 7,61 A / 1750 VA
Frequency:	50-60 Hz
Test voltage:	4000 V / 50 Hz

Application:	The transportable isolating transformer guaranteed the safe galvanic isolation of the input and output sides Isolating transformers may be used to set up protective separation as a protective measure in accordance with VDE 0100. Only one device on each secondary winding of an isolation transformer may be connected in accordance with BGI 594.
--------------	--

Optional on request:	Sockets USA, UK, UAE, China, France, Switzerland, Brasil, Australia, etc, country-specific voltages, safety transformers with low voltage < 50 V, three-phase version, CEE or low voltage sockets
----------------------	---



Subjects to change!