
Type designation: Isolating transformer 3500 VA / 230 V / 230 V
Type: ETTV 3500
Item number: 01-13500

Standard: VDE 0570 Teil 2-4, EN 61558-2-4, IEC 61558-2-4
Version: transportable
Construction: encapsulated with high insulating polyurethane, carrying handle
Short circuit strength: non inherently short circuit proof
Max. ambient temperature: + 40°C
Insulation class: E
Protection index: IP 54
Safety class: 2
Weight: 45 kg
Dimensions approximately: 240 x 280 x 350 mm (width x height x depth)
Connection input: 2m power cord with contour plug CEE 7/17
Connection output: SCHUKO socket, PE potential free
Protection input: Thermal protection switch

Power: 3500 VA
Input voltage: 230 V
Output voltage: 230 V
Output current: 15,22 A
Frequency: 50-60 Hz
Test voltage: 4000 V / 50 Hz

Application: The transportable isolating transformer guaranteed the safe galvanic isolation of the input and output sides
Isolating transformers may be used to set up protective separation as a protective measure in accordance with VDE 0100. Only one device on each secondary winding of an isolation transformer may be connected in accordance with BGI 594.

Optional on request: Sockets USA, UK, UAE, China, France, Switzerland, Brasil, Australia, etc, country-specific voltages, safety transformers with low voltage < 50 V, three-phase version, CEE or low voltage sockets



Subjects to change!