


HEOL Spezialtransformatoren

Quality Made in Germany



Type designation: Isolating transformer 400 VA / 230 V-200 VA / 230 V-200VA
Type: ETTV 400
Item number: 1038

Standard: VDE 0570 Teil 2-4, EN 61558-2-4
Version: transportable, outputs are galvanically isolated against each other
Construction: encapsulated with high insulating polyurethane, carrying handle
Short circuit strength: non inherently short circuit proof
Max. ambient temperature: + 40°C
Insulation class: E
Protection index: IP 54
Safety class: 2
Weight approximately: 10,7 kg
Dimensions approximately: 260 x 190 x 160 mm (width x height x depth)
Connection input: 2m power cord with contour plug CEE 7/17
Connection output: SCHUKO socket, PE potential free
Short circuit strength input: Glass body fuse IEC 60127-2/3
Overload protection input: Fail-safe temperature switch
Protection output 1+2: Glass body fuse IEC 60127-2/3

Power: 400 VA
Input voltage: 230 V
Output voltage 1: 230 V / 0,87 A / 200 VA
Output voltage 2: 230 V / 0,87 A / 200 VA
Frequency: 50-60 Hz
Test voltage: 4000 V / 50 Hz

Application: The transportable isolating transformer guaranteed the safe galvanic isolation of the input and output sides.
Isolating transformers may be used to set up protective separation as a protective measure in accordance with VDE 0100. Only one device on each secondary winding of an isolation transformer may be connected in accordance with BGI 594.

Optional on request: Sockets USA, UK, UAE, China, France, Switzerland, Brasil, Australia, etc, country-specific voltages, safety transformers with low voltage < 50 V, three-phase version, CEE or low voltage sockets



Subjects to change!